



Pro-Solid



Pro-Innovation



D.I.Y Decking Tiles



Solid Square Keel



Solid Curve Keel



Metal Clips



Starter Clips



End Clip



Expansion Screw



L-Side Cover



TRU-WOODS



Technical Specifications

Specification	: 30% Grade A Recycled HDPE 60% Bamboo Fiber 10% Chemical Additives
Profile	: Pro-Solid / Pro-Inno / Decking Tile
Dimension	: Pro-Solid: 20 x 145 x 2200mm Pro-Inno: 25 x 145 x 2200mm Decking Tile: 22 x 310 x 310mm
Packaging	: Pro-Solid: 210 pcs / pallet Pro-Inno: 168 pcs / pallet Decking Tile: 528 pcs / pallet
Quality standard	: ASTM / EN
Warranty	: 5 to 10 years *
Country of Origin	: China

Why TRU-WOODS?

Our decking has all the warmth and feel of wood without the associated maintenance problems, making it more durable and easier to live with, so is ideal for the residential and commercial area.



Slip Resistant

Whether wet or dry, non-splinter, concealed fixings.



Easy to Clean

No chemical cleaners required, just soap, water, a non-abrasive cloth, or simply a jet-wash.



Low Maintenance

No staining, painting or sealing required.



Resistant to Water

Low moisture content and water absorption.



Rot Resistant

No wood preservative required to extend life.



Colourfast

NO treatment required to maintain the colour. Does not 'grey' with age, as experienced with unprotected timber.



Fire Resistant

When exposed to flame, our product will self extinguish.



Environmentally Friendly

All deck board is 100% recyclable, with a natural appearance.