

## PRESTIGE SPC

- · Specialinipsunded Stone Plastic Composite board.
- Water-proof and termite-proof specs.
- · Will not swell when exposed to water.
- Will not expand and contract.
- · No need for transition strips in large
- Easy to install glueless Valinge Loc profile
- · No underlayment required (optional).
- · Can be installed over other hard surface flooring or sub-floor.
- Minimal sub-floor preparation.
- · No need to acclimate floor.
- No telegraphic effect from subfloor imperfections.
- Composite core contains stone powder +
- · Provide a warm and quiet feel floor.

## **Technical Specifications**

Dimension : 5.0mm x 180mm x 1230mm

Wear Layer : 0.55mm

Finishes : UV Lacquer ceramic coating

Embossing: Woodgrain texture Profile Valinge 2G Loc : 8 per pack (19.06 sqft), Packaging

: 15 years Light Commercial and Warranty

25 years Residential

## What's make PRESTIGE SPC so unique and revolutionary?





















## ELEGANTFLOOR

Lot 3, 1st Floor, Block E, Lintas Jaya Uptownship, Jalan Lintas, Kepayan Highway, 88200 Kota Kinabalu, Sabah, Malaysia. T 088 720 378 M 016 844 2233 (Ms. Man)

E floor.elegant@yahoo.com W http://www.elegantfloorkk.com





PS 1809 Expresso Oak



PS 2481 Americano Oak




PS 2565 Cappuccino Oak

Method



Position the 2 planks



PS 2129 Latte Oak



PS 2482 Mocha Oak



PS 802910 Caramel Oak



Angle the second plank and align the interlocking strips



Press down and lock into place